

Bio Clean Industrial

Advanced Water-Based Industrial Degreasing Solution

FlameOFF® Bio Clean Industrial is an advanced formulation in aqueous industrial cleaning chemistry. Engineered as a water-based degreasing solution, it is optimized for the removal of a wide spectrum of natural and hydrocarbon-based contaminants—ranging from light residues to heavy sludge deposits—on both uncoated substrates and painted surfaces. This product is an environmentally friendly alternative to solvent and corrosive cleaning agents.

INDUSTRIAL APPLICATIONS

Our high-performance cleaner is formulated with non-toxic, non-hazardous ingredients, enabling safe deployment in various industrial sectors:

OIL AND GAS

Decontamination of drilling equipment and hydrocarbon-exposed surfaces including soil and waterways

AUTOMOTIVE

Engine block degreasing, drivetrain cleaning and other heavy equipment

MANUFACTURING

Removal of machining lubricants, cutting fluids, and industrial grease from equipment

AEROSPACE

Surface cleaning of aircraft parts and ground support equipment (SAE AMS 1550B)

PHYSICAL CHARACTERISTICS

Appearance	Light Brown Liquid	VOC	0 g/L
Odor	Unscented	Weight	8.34 lb/gal, 1 kg/L
Base Type	Water-based	Density	~1005 @ 20°C, kg/m ³
Flash Point	N/A	pH	12.0 to 13.0

SURFACE PREPARATION

Test Area: Always test FlameOFF® Bio Clean Industrial in an inconspicuous location to ensure performance and compatibility with the surface.

Ensure the surface is free and clear of dirt and debris. Pre-rinse with clean water to remove excess contaminants if feasible before applying FlameOFF® Bio Clean Industrial.

APPLICATION INSTRUCTIONS

1. Remove loose dirt and debris; pre-rinse with clean water if needed
2. Shake the container for several minutes
3. Spray, brush, or immerse the contaminated equipment or surface with FlameOFF® Bio Clean Industrial
4. Let the product sit for several minutes to penetrate and break down hydrocarbons, oils, grease, or machining residues
5. For heavily soiled areas, reapply the product and rinse again

APPLICATION NOTES

FlameOFF® Bio Clean Industrial may be applied by spray, immersion, high-pressure wash, or ultrasonic cleaning, using 5-75% dilution as needed. Allow brief contact time, agitate if required, and rinse thoroughly with clean water.

APPLICATION METHODS

FlameOFF® Bio Clean Industrial may be applied by:

- Spray application
- Immersion
- High-pressure wash
- Ultrasonic cleaning

CARE & MAINTENANCE

- Store in a cool, dry place with the container tightly closed
- Avoid contamination of the solution during use
- Dispose of spent solutions according to local regulations

CAUTIONS

- Avoid contact with eyes and prolonged skin exposure
- Do not ingest
- Always wear appropriate protective equipment required by authority in your region
- Seek medical attention if needed
- Keep out of reach of children

FlameOFF® Coatings

info@flameoffcoatings.com | www.flameoffcoatings.com

Contact technical sales for product inquiries and large volume orders.

Disclaimer: The information contained herein is believed to be accurate as of the date of preparation. FlameOFF® Coatings makes no warranty, express or implied, regarding the accuracy of this data or the results to be obtained from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. FlameOFF® Coatings assumes no liability for damages of any kind, and users assume all risk and liability for any use of this information.